

AERO 4T 15W-50

Description

High-performance aircraft motor oil based on synthetic technology. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are guaranteed. Specially formulated additives result in high shear stability and in combined systems ensure particular protection for the transmission.



Properties

- optimum lubrication under all operating conditions
- high wear resistance
- high engine cleanliness
- optimum stability to aging
- high shear stability

Specifications and approvals:

API SL • JASO MA2

Technical data

Viscosity class	15W-50
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	139 mm ² /s DIN 51562
Viscosity at 100 °C	18,8 mm ² /s DIN 51562
Viscosity index	153 DIN ISO 2909
Flash point	240 °C DIN ISO 2592
Color number (ASTM)	3,5 DIN ISO 2049

Areas of application

Developed for air and water-cooled 4-stroke light aircraft engines exposed to normal to extreme operating conditions. Suitable for engines with or without a slip clutch. LIQUI MOLY recommends this product for series 912 and 914 Rotax engines - complies with Rotax Service Instructions SI-912-016 and SI-914-019

Application

The operating instructions of the engine manufacturers must be followed.

Available pack sizes

1 l Canister plastic	5912 D-GB-F
4 l Canister plastic	5913 D-GB-F
20 l Canister plastic	5914 D
60 l Drum sheet metal	5915 D
205 l Drum sheet metal	5916 D

Our information is based on thorough research and may be considered reliable, although not legally binding.